



1. ALL VALUES:
 A. MULTIPLIER AT DECIMAL LOCATION, i.e.:
 $3.6k\Omega = 3 \cdot 10^3 \Omega$, $0.047\mu F = 4.7 \cdot 10^{-2} F$, $22\mu F = 22 \cdot 10^{-6} F$
 B. $p=10^{-12}$, $n=10^{-9}$, $\mu=10^{-6}$, $m=10^{-3}$, $k=10^3$, $M=10^6$, $G=10^9$
2. R1 & 8 ARE R2 & 7 ON 40A
3. ALL SPLIT VOLTAGES ARE $\pm 0dB$
4. W25-27 INSTALLED ON "B" - $-40dB$ OR OFF
5. WHEN CALIBRATING, USE GND. ON DRIVER/DISPLAY BD.
6. \leftarrow = FEMALE/T.B.
 \rightarrow = MALE
 \rightarrow = 1N4001
 \rightarrow = 1N4148/914
 \oplus = CW85(JKL), 8V/50ma.
7. C102 USED ON 0
8. ON MODEL 10-R
9. C9 (ON SIGNAL E)
10. C5 & 6 (ON DRIVE
11. ALL pF MONOS

NOTES: UNLESS OTHERWISE SPECIFIED

